

Best price-performance ratio

CONCENTRATED ON THE ESSENTIALS

You want an easy solution?
Get informed now!

bema GmbH Maschinenfabrik

Recker Str. 16 | 49599 Voltlage - Weese | Germany
phone: +49 5467.9209-0 | fax: +49 5467.9209-20
info@bema-sweeper.com

www.bema-sweeper.com

 **YouTube**



bema 11 Multi-Clean - Push broom
bema 20 Agrar-Line - Special edition

Your local bema dealer:

bema[®]

A clean product line.

MADE IN GERMANY



bema 11 Multi-Clean

Working widths: 1500, 2000, 2500, 3000 mm

- **Strong cleaning performance:**
Brush kit with 11 rows (PPN, height 280 mm) of bristles for coarse and fine dirt (fine & coarse bristles mixed; also only fine or only coarse available); very good selfcleaning properties due to the pendulum suspension of each row
- **Robust and stable construction:**
Very robust and torsion-resistant design; supporting legs optionally available
- **Convenient handling:**
Comfortable and quick attachment and detachment: easy to change bristle rows; maintenance-free
- **Versatile applicable:**
For example for dirt, mud, grid, corn, silage; brushing of sand and grid at pavement work; brushing of or snow in winter service

Installation on: Wheel loader, telehandler, yard loader, forklift, excavator, tractor, compact tractor



SIMPLY EFFECTIVE



bema 20 Agrar-Line

Roller brush Ø 520 mm (PPN); working width: 2300 mm

- **Tackles large amounts of dirt:**
Collection container volume approx. 245 litres; emptying of the collection container via rope (mechanical)
- **Stable and durable design:**
Very robust and torsion-resistant machine housing, hydraulic drive with strong Gerotormotor
- **Standard equipment:**
Toolless adjustment of the collection container; series painting Agrar-Line green; adjustable wheels Ø 200 x 50 mm; supporting legs and lifting eyes
- **Optional equipment:**
Heavy duty support wheels Ø 200 x 50 mm (industrial quality)
Add-on kits for self-assembly: Hydraulic rotary side brushes Ø 600 mm, right and/or left, incl. bema SideControl (PPN, steel/PPN, steel flat wire/PPN, steel flat wire, weed removal trim); 3rd support heavy duty wheel Ø 200 x 50 mm (necessary for front operation)

Installation on: Rear of the tractor (three point linkage), mechanical swivelling (both sides)

