



NEW

bema Kommunal 450 Dual

ULTRALIGHT & COMPACT

Main brush Ø 450 mm with different trims

The sweeper bema Kommunal 400 Dual is attached very close to smaller municipal vehicles, compact tractors, yard loaders and also front mowers. Despite its light weight, the bema Kommunal 400 Dual is extremely robust and provides convincing performance with optimum sweeping results, even in snowy conditions.


FEATURES

- ✓ **Adapted for municipal requirements:**
The compact attachment ensures optimal weight distribution close to the axis. The low mounting height guarantees a good view from the carrier vehicle. All mountings with 3D compensation.
- ✓ **Multiply deployable and optimal power transmission:**
Optional mechanical drive via a drive shaft or hydraulic drive via a powerful gerotor motor without any additional charge. The incline of the drive can be adjusted, so that the position can be adjusted exactly to the carrier vehicle.
- ✓ **Maintenance-friendly in year-round use:**
Both parts and the main brush can be quickly replaced. The sweeper can be used all year round thanks to the various trims
- ✓ **Maximum flexibility:**
The collection container in Dual version enables easy switching between free sweeping and collecting dirt without changeover time. The sweeper swivels mechanically or optionally hydraulically.

CARRIER VEHICLES

-  Yard loader
-  Compact tractor (front)
-  Municipal vehicle
-  Front mower

OPTIONAL EQUIPMENT

-  Water spray unit
main brush, rotary side brushes
-  Rotary side brushes
with bema SideControl
-  Mechanical drive
incl. drive shaft
-  Hydraulic swivel device
20° to the left/right
-  bema Weed brush
optional main brush
-  bema PowerPack
hydraulic power unit
-  bema Control
from 3 functions available



bema Kommunal 450 Dual, mechanical drive



bema Kommunal 450 Dual, hydraulic swivel device



bema Kommunal 450 Dual with rotary side brush and water spray unit



Rotary side brush with water spray unit

TECHNICAL DATA

Maschine type	bema Kommunal 450 Dual		
Working width	1250 mm	1400 mm	1550 mm
Drive	Your choice: mechanical drive incl. drive shaft (the incline of the drive can be adjusted) or hydraulic drive via powerful Gerotormotor with drive shaft Ø 25 mm (heavy series);		
Minimum hydraulic power of the carrier vehicle	15 l/min		20 l/min
Minimum engine power of the carrier vehicle	Compact tractors with more than approx. 15 PS		
Weight basic machine (approx.)	118 kg	123 kg	127 kg
Volume / weight (approx.) collection container Dual	84 l / 38 kg	94 l / 42 kg	104 l / 47 kg
Main brush Ø 450 mm	Universal brush PPN spiral fitting (also for use in snow). Optional: steel flat wire/PPN spiral fitting, bema Weed brush (Ø 400 mm incl. reinforced drive); easy change of the main brush		
Brush speed	Recommended 150 to max. 250 rpm		
Wheels	Heavy-load wheels Ø 160 x 50 mm (industrial version)		
Rotary side brushes Ø 480 mm (optional equipment)	Hydraulic drive incl. bema SideControl (comfort operation, combines 3-way valve and speed controller); rotary side brushes are available for the right and/or left side. Selectable brushes: PPN, steel/PPN, steel flat wire/PPN, steel flat wire		
Water spray unit (optional equipment)	240 l water tank, tank filter and 12 V pressure pump - rear attachment; (direct injection of water into the main brush and rotary side brushes)		
Further attachments and equipment, as well as special constructions on request. Technical data and weight measurements are approximate and non-binding. Weight measurements without special equipment and attachment. Mistakes and errors reserved. © bema GmbH Maschinenfabrik (2021.07)			

FEATURES IN DETAIL



Heavy-load wheels Ø 160 x 50 mm



Water tank at the rear



Hydroblock and bema SideControl